

# 3050830 AC Controlled Power Switch Module




- 3.3" x 3.3" x 1.3" Black ABS Plastic Enclosure with **Mounting Flanges**
- Double-Insulated Enclosure, No Equipment Grounding Conductor
- IP45 Ingress Protection
- UL Rated 12 Amp Power Relay with 5kV Coil to Contact **Isolation**
- 5' Long #14/2 AWG SO Cord with 2 Prong Plug
- 4 Pin 13 Amp Deutsch Power Output Connector
- Custom Overlay

### ECHNICAL SPECIFICATIONS

Operating Voltage	120VAC coil
Current Consumption	15mA
Operating Temp. Range	-40°C to +85°C (-40°F to +185°F)
Storage Temp. Range	-40°C to +85°C (-40°F to +185°F)
Ingress Protection	IP45
Electrical Protection	Class II Reinforced Insulation

## **PART NUMBERS**

Description	IC Part Number
AC Controlled Power Switch Module	3050830
5 ft. Wire Harness with DT06-4S Connector	4000687



# **AUTOMATIC DC POWER SOURCE** CT DESI

The Innovative Controls Inc. 3050830 AC Controlled Power Switch Module automatically selects the DC power source for the sanitizer based on the state of the vehicle shore power.

When the vehicle is plugged into AC shore power, the sanitizer is powered directly from the battery. When the AC shore power is disconnected, the sanitizer is powered from the vehicle ignition circuit.

The AC Controlled Power Switch Module contains hazardous voltage. Contact with internal parts may cause electrical shock and injury. Disconnect power before removing cover. No user serviceable parts inside.

### MENSIONS

